

# NOVA PC 9050V

Polycarbonate  
NOVA Polymers, Inc.

Message:

NOVA PC 9050V is a polycarbonate (PC) material. This product is available in North America and is processed by injection molding.

The main features of NOVA PC 9050V are:

flame retardant/rated flame

Flame Retardant

General Information			
UL YellowCard	E143392-223287		
Features	Flame retardancy		
UL File Number	E143392		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.20	g/cm <sup>3</sup>	ASTM D792
Melt Mass-Flow Rate (MFR) (300°C/1.2 kg)	10	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield, 3.18 mm)	62.1	MPa	ASTM D638
Flexural Modulus (3.18 mm)	2210	MPa	ASTM D790
Flexural Strength (Yield, 3.18 mm)	89.6	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	640	J/m	ASTM D256
Flammability	Nominal Value		Test Method
Flame Rating	V-0		UL 94
1.57 mm	5VB		UL 94
	V-0		
3.18 mm	5VA		UL 94
Additional Information			

Moisture Content, ASTM D 4019-88: <0.04 %

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

