

Nipol® LX854E

Latex
Zeon Corporation

Message:

Acrylate latex
Characteristics
Stronger self-crosslinking than LX852B. Low formaldehyde.
Soft type.
Applications
Non-woven fabrics for wood floor cushions, resin cottons, and clothing.
Fabric labels(care instruction labels), and canvases (impregnated).

General Information			
Features	Copolymer		
	Crosslinkable		
	Soft		
Uses	Fabrics		
	Labels		
	Nonwovens		
Physical	Nominal Value	Unit	
Solution Viscosity	25	mPa·s	
pH	6.5		
Surface Tension	27	mN/m	
Total Solids	45	%	
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	-10.0	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT