Yuyao PPO SE1X701

Polyphenylene Ether + PS

Yuyao Tenglong Plastics Co., Ltd.

Message:

Yuyao PPO SE1X701 is a Polyphenylene Ether + PS (PPE+PS) product. It can be processed by injection molding and is available in Asia Pacific. Typical application: Electrical/Electronic Applications.

Characteristics include:

Flame Rated

Chemical Resistant

Flame Retardant

Good Dimensional Stability

Heat Resistant

General Information				
Features	Flame Retardant			
	Good Dimensional Stability			
	Good Electrical Properties			
	High Heat Resistance			
	High Rigidity			
	Low Shrinkage			
	Solvent Resistant			
Uses	Electrical Parts			
	Electrical/Electronic Applications			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.09	g/cm³	ASTM D792	
Molding Shrinkage - Flow	0.50 to 0.80	%	ASTM D955	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength	60.0	MPa	ASTM D638	
Tensile Elongation (Break)	4.0	%	ASTM D638	
Flexural Modulus	3200	MPa	ASTM D790	
Flexural Strength	90.0	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (Area)	7.00	kJ/m²	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (1.8 MPa, Unannealed)	120	°C	ASTM D648	
Electrical	Nominal Value	Unit	Test Method	
Volume Resistivity	2.3E+3	ohms·cm	ASTM D257	
Flammability	Nominal Value	Unit	Test Method	
Flame Rating			UL 94	

1.60 mm	V-0		
3.20 mm	V-0		
Injection	Nominal Value	Unit	
Drying Temperature	100 to 115	°C	
Drying Time	4.0 to 5.0	hr	
Processing (Melt) Temp	250 to 280	°C	
Mold Temperature	60.0 to 80.0	°C	
Injection Pressure	70.0 to 100	MPa	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

