Gallonprene® GP310-7502

Thermoplastic Elastomer

Shenzhen Sungallon Rubber & Plastic Corporation Limited

Message:

Gallonprene® GP310-7502 is a thermoplastic elastomer (TPE) product. It is available in Africa and the Middle East, Latin America or Asia Pacific. Gallonprene®GP310-7502 application areas include electrical/electronic applications, electrical appliances, engineering/industrial accessories and industrial applications.

Features include: Comply with REACH standard **ROHS** certification Halogen-free

General Information

NOTE 1.

2.

Features	High elasticity		
	Halogen-free		
Uses	overmolding		
	Electrical appliances		
	Industrial application		
	Mobile phone		
Agency Ratings	EC 1907/2006 (REACH)		
RoHS Compliance	RoHS compliance		
Appearance	White		
	Rough surface polishing		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.09	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	7.6	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 23°C)	75		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Break)	5.50	MPa	ASTM D412
Tensile Elongation ² (Break)	500	%	ASTM D412
Injection instructions			
Overmolding Parameters:Rear Temperature: 180°CMold Temperature: 30 to 60°CProcess	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	
Temperature: 80°CDrying Time: 4 hr	ing remperature Limit: 230 Cinjection	rressure. mighinjection speed: HighB	ack Fiessule. 20 to 50%Diying

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any

500 mm/min

500 mm/min

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



Page 2