

Softflex® 7397

Thermoplastic Elastomer

Network Polymers, Inc.

Message:

Softflex® 7397 is a Thermoplastic Elastomer (TPE) product. It is available in North America. Typical application: Engineering/Industrial Parts.

General Information			
Uses	Overmolding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity ¹	0.968	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	73		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	3.60	MPa	ASTM D412
Tensile Strength ² (Yield)	8.48	MPa	ASTM D412
Tensile Elongation (Break)	460	%	ASTM D412
Tear Strength	28.0	kN/m	ASTM D624
Compression Set	24	%	ASTM D395
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	< -60.0	°C	ASTM D746
NOTE			
1.	Method A		
2.	510 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT