

NEXUS PE HDPE-0764

High Density Polyethylene

Nexus Resin Group, LLC.

Message:

High Density Polyethylene for blow molding applications
Nexus HDPE-0764 is designed for general purpose blow molding applications requiring excellent stiffness and low taste and odor transfer.

General Information			
Features	High Stiffness		
	Low Odor Transfer		
	Low Taste Transfer		
Uses	Blow Molding Applications		
Processing Method	Blow Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.964	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.70	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	30.3	MPa	ASTM D638
Tensile Elongation (Break)	300	%	ASTM D638
Flexural Modulus	1650	MPa	ASTM D790

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT