

Borealis PP HH450FB

Polypropylene Homopolymer

Borealis AG

Message:

HH450FB is a polypropylene homopolymer intended for fibre applications.

General Information			
Additive	Anti-gas fading		
Features	Controlled Rheology		
	Gas-fading Resistant		
	Good Processability		
	High Flow		
	High Purity		
	Homopolymer		
	Narrow Molecular Weight Distribution		
Uses	Fibers		
	Spunbond Nonwovens		
Appearance	Natural Color		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	37	g/10 min	ISO 1133
Thermal	Nominal Value	Unit	Test Method
Melting Temperature (DSC)	161 to 165	°C	ISO 3146

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT