# T-Blend® 5792N-PE

### Thermoplastic Elastomer

#### **TSRC** Corporation

#### Message:

T-Blend® 5792N-PE is a Thermoplastic Elastomer (TPE) product. It can be processed by extrusion or injection molding and is available in Asia Pacific. Applications of T-Blend® 5792N-PE include handles, bags/liners, business/office goods, consumer goods and engineering/industrial parts. Characteristics include: Chemical Resistant Eco-Friendly/Green Fast Molding Cycle Food Contact Acceptable Good Adhesion

General Information				
Features	Fast Molding Cycle			
	Food Contact Acceptable			
	Good Adhesion			
	Good Chemical Resistance			
	Good Colorability			
	Good Weather Resistance			
	Non-Toxic			
	Recyclable Material			
Uses	Flexible Grips			
	Household Goods			
	Liners			
	Overmolding			
	Power/Other Tools			
	Sporting Goods			
	Stationary Supplies			
	Toothbrush Handles			
	Toys			
Agency Ratings	FDA Food Contact, Unspecified Rating			
Appearance	Clear/Transparent			
Processing Method	Extrusion			
	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	0.870 to 0.910	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (180°C/5.0 kg)	40 to 70	g/10 min	ASTM D1238	
Hardness	Nominal Value	Unit	Test Method	

Durometer Hardness (Shore A)	55 to 59		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Break)	6.28	MPa	ASTM D412
Tensile Elongation (Break)	760	%	ASTM D412
Tear Strength	24.5	kN/m	ASTM D624
Additional Information	Nominal Value		
Substrate	PP		
Injection	Nominal Value	Unit	
Processing (Melt) Temp	180 to 210	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

