

Sylvin 5132-90UV Clear

Polyvinyl Chloride
Sylvin Technologies Incorporated

Message:
Sylvin 5132-90UV Clear Is A Clear Vinyl Compound Formulated For Wire & Cable Applications That Require A UV Stabilizer.This Compound Can Be Color Matched To A Variety Of Colors.

General Information	
Additive	UV Stabilizer
Features	Good UV Resistance
Uses	Wire & Cable Applications
Appearance	Clear/Transparent Colors Available

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.24	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	90		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	18.6	MPa	ASTM D638
Tensile Elongation (Break)	350	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	60.0	°C	ASTM D794
Melting Temperature	171 to 182	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT