

Moldex® QS981A/M151

Polyolefin

Mitsubishi Chemical Corporation

Message:

Moldex® QS981A/M151 is a Polyolefin material. It is available in Asia Pacific. Primary attribute of Moldex® QS981A/M151: Crosslinkable.

Typical application of Moldex® QS981A/M151: Hose/Tubing

General Information			
Features	Crosslinkable		
Uses	Hose		
	Tubing		
Physical	Nominal Value	Unit	Test Method
Density	0.890	g/cm ³	ISO 1183
Gel Content ¹ (120°C)	90	%	
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	79		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress			ISO 527-2
Yield, 23°C	3.70	MPa	
Yield, 80°C	1.60	MPa	
Break, 23°C	21.0	MPa	
Break, 80°C	4.50	MPa	
Tensile Strain			ISO 527-2
Break, 23°C	580	%	
Break, 80°C	650	%	
NOTE			

1. In Xylene, 20 hr

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT