# Varcum 29109

#### Phenolic

## **Durez Corporation**

#### Message:

Varcum 29109 is a thermosetting phenolic resin in lump form.

Varcum 29109 is recommended for use in metal coating applications.

The use of modifying agents tend to reduce the maximum chemical resistance and, therefore, the incorporation of such agents is not generally recommended. Alcohol and/or ketone solvent systems are required with this product; the use of hydrocarbon solvents is not pratical.

General Information			
Features	Good Chemical Resistance		
Uses	Coating Applications		
Forms	Lump		
Physical	Nominal Value		Test Method
Viscosity - G&H	V		Internal Method
Softening Point - B&R	73	°C	Internal Method
Thermoset	Nominal Value	Unit	
Post Cure Time (150°C)	0.018	hr	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

