

Paracril® 34PE40N

Acrylonitrile Butadiene Rubber

INSA

Message:

Description:

Plasticized with 50 parts of dinp .

High molecular weight polymer.

Fast mixing.

Cold polymerized.

Non staining stabilizer.

Applications:

Low durometer roll covers.

Footwear.

Highly plasticized recipes.

Blend to improve abrasion resistance in nbr recipes.

General Information	
Features	Fast Cure
	High Molecular Weight
	Plasticized
Uses	Footwear
	Protective Coverings
	Rollers

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.980	g/cm ³	ASTM D297
Mooney Viscosity (ML 1+4, 100°C)	33 to 47	MU	ASTM D1646
ACN Content - Bound	32.5 to 35.5	wt%	Internal Method
Ash Content	< 0.8	wt%	ASTM D5667
Volatile Matter	< 1.0	wt%	ASTM D5668

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT