

# Microthene® MP652762

High Density Polyethylene

LyondellBasell Industries

## Message:

Microthene MP652762 is a hexene HDPE powder selected by customers for rotationally molding large tank applications. MP652762 is a UV-stabilized, 35 mesh powder and is also available in pellet form as Petrothene GA652762.

| General Information                       |                       |                   |
|---|-----------------------|-------------------|
| Additive                                  | UV stabilizer         |                   |
| Features                                  | hexene comonomer      |                   |
|   | Good UV resistance    |                   |
| Uses                                      | Industrial water tank |                   |
|   | Container             |                   |
|   | Water tank            |                   |
| Forms                                     | Powder                |                   |
| Processing Method                         | rotomolding           |                   |
| Physical                                  | Nominal Value         | Unit              |
| Density (23°C)                            | 0.942                 | g/cm <sup>3</sup> |
| Melt Mass-Flow Rate (MFR) (190°C/2.16 kg) | 2.0                   | g/10 min          |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

