

ADENE ONOBG

Polypropylene Copolymer

A.D. Compound spa

Message:

ADENE ONOBG is a Polypropylene Copolymer (PP Copolymer) material. It is available in Europe or North America. Primary attribute of ADENE ONOBG: Copolymer.
Typical application of ADENE ONOBG: Automotive

General Information			
Features	Copolymer		
Uses	Automotive Applications		
Appearance	Black		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	10	g/10 min	ISO 1133
Ash Content	0.0	%	ISO 3451-1
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	920	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	12	kJ/m ²	ISO 180/1A
Unnotched Izod Impact Strength (23°C)	No Break		ISO 180/1U
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	47.0	°C	ISO 75-2/A
Vicat Softening Temperature	74.0	°C	ISO 306/B

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT