## ISOTHANE® 2095A-M1

Thermoplastic Polyurethane Elastomer (Polycaprolactone)

Great Eastern Resins Industrial Co., Ltd. (GRECO)

## Message:

ISOTHANE 2095A-M1 product is polycaprolactone based thermoplastic polyurethanes. It exhibits high elasticity, hydrolysis resistant, oil resistance and low compression set. This product is particularly suitable for oil seals production. The product can be injection molded. Suggested Applications:

Gaskets, Oil Rings, Seals, Packing, Boots, Pads, Hoops, Tubes, Shoes.

General Information					
Features	Low compressive deformability				
	High elasticity				
	Hydrolysis resistance				
	Oil resistance				
	General				
Uses	Packaging				
	Washer				
	Pipe fittings				
	Seals				
	General				
	Footwear				
Processing Method	Injection molding				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.20	g/cm³	ASTM D792		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A)	94		ASTM D2240		
Elastomers	Nominal Value	Unit	Test Method		
Tensile Stress			ASTM D412		
50% strain	12.0	MPa	ASTM D412		
100% strain	15.0	MPa	ASTM D412		
300% strain	35.0	MPa	ASTM D412		
Tensile Strength	56.0	MPa	ASTM D412		
Tensile Elongation (Break)	390	%	ASTM D412		
Tear Strength <sup>1</sup>	164	kN/m	ASTM D624		
Compression Set			ASTM D395B		
70°C, 24 hr	29	%	ASTM D395B		
100°C, 24 hr	41	%	ASTM D395B		
Bayshore Resilience	34	%	ASTM D2632		
Injection	Nominal Value	Unit			

Rear Temperature	195 - 205	°C	
Middle Temperature	200 - 210	°C	
Front Temperature	200 - 210	°C	
Nozzle Temperature	190 - 200	°C	
NOTE			
1.	C mould		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

