

POLYPRO® 5014L HPT

Polypropylene Homopolymer
YUHW A Korea Petrochemical Ind. Co., Ltd.

Message:

POLYPRO® 5014L HPT is a Polypropylene Homopolymer (PP Homopolymer) material. It is available in Asia Pacific.

Important attributes of POLYPRO® 5014L HPT are:

RoHS Compliant
High Purity
Homopolymer
Typical application of POLYPRO® 5014L HPT: Film

General Information			
Features	General Purpose		
	High Purity		
	Homopolymer		
	Metallizable		
Uses	Bi-axially Oriented Film		
	Film		
RoHS Compliance	RoHS Compliant		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.2	g/10 min	ASTM D1238
Ash Content	10 to 20	ppm	Internal Method
Catalyst Residue			Internal Method
AI (XRF)	2 to 4	ppm	
CI (XRF)	1 to 3	ppm	
Isotactic Index	96	%	Internal Method
Thermal	Nominal Value	Unit	Test Method
Peak Melting Temperature	162 to 165	°C	ASTM D3418
Electrical	Nominal Value		Test Method
Dielectric Constant	2.25		Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

