Moplen EP6051

Polypropylene

LyondellBasell Industries

Message:

Polypropylene coating with slip additive for BOPP/CPP film - developmental grade

General Information		
Features	smoothness	
Uses	Films	
	Laminate	
	Coating application	
Processing Method	Extrusion coating	
	cast film	
Physical	Nominal Value	Unit
Density	0.900	g/cm³
Melt Mass-Flow Rate (MFR) (230°C/2.16		
kg)	18	g/10 min
Mechanical	Nominal Value	Unit
Tensile Strength (Yield)	20.0	MPa
Tensile Elongation (Yield)	16	%
Flexural Modulus	640	MPa
Impact	Nominal Value	Unit
Notched Izod Impact (23°C)	32	J/m
Thermal	Nominal Value	Unit
Heat Deflection Temperature	77	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

