Zhongfa PP GR-30+

Polypropylene

Yuyao Zhongfa Engineering Plastics Co. Ltd.

Message:

Zhongfa PP GR-30 + is a polypropylene material, and the filler is 30% glass fiber reinforced material. This product is available in the Asia-Pacific region and is processed by injection molding. The main features of Zhongfa PP GR-30 are: chemical resistance Heat resistance Heat resistance Typical application areas include: electrical appliances industrial applications Automotive Industry

| Filler / Reinforcement | Glass fiber reinforced material, 30% filler by weight | | |
|---|---|-------|-------------|
| Features | Good liquidity | | |
| | Good chemical resistance | | |
| | Heat resistance, medium | | |
| | | | |
| Uses | Electrical appliances | | |
| | Industrial application | | |
| | Application in Automobile Field | | |
| Forms | Particle | | |
| Processing Method | Injection molding | | |
| Physical | Nominal Value | Unit | Test Method |
| Specific Gravity | 1.16 | g/cm³ | ASTM D792 |
| Molding Shrinkage - Flow | 0.40 - 0.70 | % | ASTM D955 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Strength | 70.0 | MPa | ASTM D638 |
| Flexural Modulus | 3800 | MPa | ASTM D790 |
| Flexural Strength | 90.0 | MPa | ASTM D790 |
| Thermal | Nominal Value | Unit | Test Method |
| Deflection Temperature Under Load (0.45 MPa, Unannealed) | 150 | °C | ASTM D648 |
| Additional Information | | | |
| Notched Izod Impact, ASTM D256: 5 kJ/m ² U | nnotched Izod Impact, ASTM D256: 16 | kJ/m² | |
| Injection | Nominal Value | Unit | |
| Drying Temperature | 90.0 - 95.0 | °C | |
| Drying Time | 2.0 - 3.0 | hr | |
| Processing (Melt) Temp | 215 - 245 | °C | |
| Mold Temperature | 45.0 - 80.0 | °C | |

| Injection | Pressure |
|-----------|----------|
|-----------|----------|

MPa

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

