

SolVin 370HD

Polyvinyl Chloride

INOVYN

Message:

Polyvinyl chloride made by emulsion polymerisation for plastisol preparation.

MAIN APPLICATIONS

Spread coating :

artificial leather compact layer

artificial leather foam layer

artificial leather automotive

Moulding and dipping.

Spraying :

automotive sealants.

ADVANTAGES

Low volatile content in the fogging test.

Very white foams.

Pseudoplastic rheological behaviour.

General Information			
Uses	Automotive Applications		
	Foam		
	Sealants		
	Synthetic Leather		
Appearance	White		
Processing Method	Coating		
	Plastisol		
	Spraying		
Physical	Nominal Value	Unit	Test Method
K-Value	70.0		ISO 1628-2
Sieve Analysis - Retained on 0.125 mm sieve	< 0.150	g/kg	ISO 787-18
Volatile Matter	< 0.30	%	ISO 1269

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT