

# ASACLEAN™ GL2

Proprietary

ASACLEAN - Sun Plastech Inc.

## Message:

PURGE COMPOUND FOR SCREW AND BARREL

Universal grade for standard polymers

Temperature range: 180°C - 360°C

ASACLEAN ® GL2 is especially designed to purge standard polymers. The fields of appliance are

Injection Moulding

Extrusion

It is characterized by the well known ASACLEAN ® purging power and efficiency. ASACLEAN ® GL2 is neither abrasive nor corrosive and is applicable for

Colour Changes

Material Changes to standard polymers

"Sealing"

Hot Runner Cleaning

Contact:

VELOX GmbH

Tel: +49 - (0)40 - 369 688 - 0

eMail: [info@velox.com](mailto:info@velox.com)

Website: <http://www.velox.com>

General Information	
Features	Non-Corrosive
Uses	Purging Compound
Forms	Pellets
Processing Method	Extrusion
	Injection Molding

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

