

HIPOLEN P® EH 8

Polypropylene Homopolymer

HIPOL A.D.

Message:

HIPOLEN P®EH 8 is a polypropylene homopolymer (PP Homopoly) product. It can be processed by extrusion and is available in Africa and the Middle East or Europe. HIPOLEN P®The application areas of EH 8 include containers and water pipes/pipes/drinking water.

Features include:

Good stiffness

Heat resistance

General Information			
Features	Rigid, good		
	Heat resistance, high		
Uses	Piping system		
	Container		
Forms	Particle		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.900	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/1.2 kg)	0.50	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Elongation (Break)	38	%	ASTM D638
Flexural Modulus	1500	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	65	J/m	ASTM D256
Additional Information			

Thermo Stability, 150°C: 1000 hrs

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT