

Formolon® 165

Polyvinyl Chloride Alloy

Formosa Plastics Corporation, U.S.A.

Message:

F-165 has been designed to meet the processing and finished product requirements of the vinyl floor tile industry. Floor tiles made with F-165 offer excellent abrasion and indentation resistance.

General Information			
Features	Good Abrasion Resistance		
Agency Ratings	EC 1907/2006 (REACH)		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.63	g/cm ³	ASTM D1895A
K-Value ¹ (25°C)	52.0		
Vinyl Acetate Content	13.0	wt%	
Inherent Viscosity	0.55		ASTM D1243
Relative Viscosity	1.65		
Sieve Analysis ²	100	%	ASTM D1921
Volatiles	0.70	%	
NOTE			
1.	0.5 g/100 cc in Cyclohexanone		
2.	Through 40 Mesh Screen		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT