

Selvol™ 540S

Polyvinyl Alcohol
Sekisui Chemical Company, Ltd.

Message:

Selvol™ 540S is a Polyvinyl Alcohol (PVOH) product. It can be processed by coating and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Applications of Selvol™ 540S include construction applications and coating applications. Primary characteristic: eco-friendly/green.

General Information		
Features	Biodegradable	
	Water Soluble	
Uses	Building Materials	
	Coating Applications	
	Construction Applications	
Forms	Granules	
Processing Method	Coating	
Physical	Nominal Value	Unit
Solution Viscosity ¹	45 to 55	mPa · s
Ash Content	< 0.5	wt%
Particle Size Distribution		
-- ²	< 0.10	%
-- ³	< 1.0	%
pH - 4% Solution	4.5 to 6.5	
Volatile Matter		
--	< 5.0	wt%
Organic	< 1.0	wt%
Hydrolysis ⁴	87 to 90	%
Methanol Extractables	< 0.9	wt%
NOTE		
1.	4%	
2.	Retained 40 mesh	
3.	Retained 80 mesh	
4.	Mole	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

