

# ALKAMIX™ MB6006

Linear Low Density Polyethylene

Qenos Pty Ltd

## Message:

ALKAMIX MB6006 is a processing aid masterbatch based on a fluoropolymer compound at a concentration of 5 percent. ALKAMIX MB6006 can be added to linear low density polyethylene (LLDPE) during extrusion to eliminate melt fracture (Sharkskin) type extrusion defects. The level required will vary according to extrusion equipment and type of LLDPE being used, however the recommended addition level is between 1 and 2 percent. ALKAMIX MB6006 is compatible with the process aid used in Alkatuff film polymers. The maximum level of addition of MB6006 based on both good manufacturing practice and to ensure conformance to the requirements to the United States Food and Drug Administration Regulations CFR21 is 5 percent, when added to a polyethylene formulation free of any other additives.

General Information			
Uses	Blending		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.945	g/cm <sup>3</sup>	ASTM D1505

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT