# ACRYLITE® Film White WF002

#### PMMA Film

### **Evonik Cyro LLC**

#### Message:

ACRYLITE® Film WF002 is a high weather resistant, glossy and white acrylic film for graphic printings and high quality laminations.

Due to its excellent performance under long term weathering and UV light exposure, ACRYLITE® Film WF002 does not present color change or yellowing. Its glossy and very smooth surface leads the film to provide an excellent printing quality.

#### Application

ACRYLITE® Film WF002 can be used to be printed on as high quality film decoration and then laminated on different polymeric films and sheets. Laminated decoration films protected by ACRYLITE® are suitable for a wide range of molding processes such as thermoforming and insert molding. ACRYLITE® Film WF002 can be used as a single face layer in high UV and weathering resistant durable labels and tapes without the need for an overlay film.

General Information			
Features	Excellent Printability		
	Good UV Resistance		
	Good Weather Resistance		
	High Gloss		
Uses	Film		
	Labels		
	Laminates		
	Таре		
Appearance	White		
Forms	Film		
Processing Method	Laminating		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.28	g/cm³	DIN 53479
Surface Tension	50	mN/m	DIN 53364
Accelerated Weathering Resistance - method A, cycle 1, 65% RH <sup>1</sup>	No Visible Change		ISO 4892-2
Color Coordinate			DIN 5033
Х	0.365		
у	0.367		
Films	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	33.0	MPa	ISO 527-3
Tensile Elongation			ISO 527-3
Yield	5.0	%	
Break	> 50	%	
Thermal	Nominal Value	Unit	Test Method
Glass Transition Temperature	95.0	°C	ISO 11357-2
NOTE			

1. 10,000 hr

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

