

Europrene Latice® 5583

Emulsion Styrene Butadiene Rubber

Versalis S.p.A.

Message:

Europrene Latice 5583 is an aqueous dispersion of a carboxylated styrene-butadiene copolymer obtained using synthetic anionic emulsifiers. It contains a non staining antioxidant

Main Applications

Europrene Latice 5583 is mainly used for paper saturation and soft handle textile impregnation.

General Information			
Additive	Antioxidant		
Features	Antioxidant		
	Copolymer		
Uses	Impregnation Applications		
	Paper Coatings		
	Textile Applications		
Appearance	White		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Bound Styrene	40.0	%	ASTM D5775
pH	8.0		ASTM D1417
Solids Content	50.0	wt%	ASTM D1417
Brookfield Viscosity ¹ (25°C)	300	mPa · s	ASTM D1417
NOTE			
1.	20 rpm		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT