

# Formolon® 265

Polyvinyl Chloride Alloy

Formosa Plastics Corporation, U.S.A.

## Message:

F-265 is a fine particle size polyvinyl chloride vinyl acetate copolymer plastisol blending resin. The product has been designed for use in application where rapid gelation and fusion is a requirement, due to low processing temperatures.

When used in combination with copolymer dispersion resin, F-265 has been successfully used in carpet backing, automotive sealants and underbody coatings as well as walk-off mats.

General Information			
Uses	Automotive Applications		
	Carpet Backing		
	Coating Applications		
	Sealants		
Agency Ratings	EC 1907/2006 (REACH)		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.60	g/cm <sup>3</sup>	ASTM D1895A
K-Value	63.0		
Vinyl Acetate Content	5.0	wt%	
Average Particle Size <sup>1</sup>	35	µm	
Inherent Viscosity	0.85		ASTM D1243
Relative Viscosity	1.95		
Sieve Analysis			ASTM D1921
-- <sup>2</sup>	100	%	
-- <sup>3</sup>	97	%	
Volatiles	0.30	%	
NOTE			
1.	Coulter Counter LS230		
2.	Through 40 Mesh Screen, Method B		
3.	Through 200 Mesh Screen, Method B		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

