

Sinvicomp SZS7068A-E5A

Flexible Polyvinyl Chloride

Teknor Apex Asia Pacific PTE. LTD.

Message:

SINVICOMP SZS7068A-E5A is a flexible polyvinyl chloride material. This product is available in the Asia-Pacific region and is processed by extrusion. The typical application field of SINVICOMP SZS7068A-E5A is: wire and cable

General Information			
Uses	Wire sheath		
Forms	Particle		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.67	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	86		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	8.00	MPa	IEC 60811-1-1
Tensile Elongation (Break)	230	%	IEC 60811-1-1
Aging	Nominal Value	Unit	Test Method
Change in Tensile Strength (115°C, 504 hr)	10	%	AS 3147/3191
Change in Ultimate Elongation (115°C, 504 hr)	25	%	AS 3147/3191
Additional Information	Nominal Value		Test Method
Loss of Mass - 5 days (115°C)	1.2 mg/cm2		AS 3147/3191

Wire Type: 3V-90

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT