

DJSilicone NE-7130

Silicone

DONGJUE SILICONE (NANJING) CO., LTD

Message:

Common silicone rubber for molding&extrusion has excellent high and low temperature resistance, electrical performance, and physical and mechanical properties. Despite of slightly worse transparency than general silicone rubber, it is more suitable for manufacturing colored products. There are two kinds of this product, namely modifying silicone rubber for molding and modifying silicone rubber for extrusion. The former can be vulcanized by DMDBH and used for manufacturing industrial accessories like keypad, seal ring and seal pad etc, while the latter can be vulcanized by DCBP and used for manufacturing wire, cable, rubber tube and rubber strip etc.

General Information			
Features	Good Colorability High Heat Resistance Low Temperature Resistant		
Uses	Seals		
Appearance	White		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.03 to 1.13	g/cm ³	ASTM D1505
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	27 to 33		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Set	< 7	%	ASTM D412
Tensile Strength (Yield)	> 5.00	MPa	ASTM D412
Tensile Elongation (Break)	> 450	%	ASTM D412
Tear Strength	> 15.0	kN/m	ASTM D624

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT