

SUPREME HIPS SH 810

High Impact Polystyrene

Supreme Petrochem Ltd.

Message:

SUPREME HIPS SH 810 is a High Impact Polystyrene product. It can be processed by injection molding and is available in Africa & Middle East, Asia Pacific, Europe, or North America. Applications of SUPREME HIPS SH 810 include consumer goods, electrical/electronic applications and food contact applications.

Characteristics include:

Food Contact Acceptable

Good Aesthetics

High Flow

Impact Resistant

General Information			
Features	Food Contact Acceptable		
	Good Impact Resistance		
	High Flow		
	Pleasing Surface Appearance		
Uses	Computer Components		
	Toys		
Agency Ratings	FDA 21 CFR 177.1640		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.05	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	7.5	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	27.5	MPa	ASTM D638
Tensile Elongation (Break)	50	%	ASTM D638
Flexural Modulus	1860	MPa	ASTM D790
Flexural Strength	36.8	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	110	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	84.0	°C	ASTM D648
Vicat Softening Temperature	100	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

