

# Paracril® BJ

Acrylonitrile Butadiene Rubber

INSA

## Message:

Description:

Excellent low temperature flexibility with oil resistance.

Good processing characteristics.

Hot polymerized.

Non staining stabilizer.

Applications:

Automotive products, seals, hoses, o-rings and packings.

Adhesives.

Sponges

Printing Blankets.

General Information	
Features	Good Processability
	Low Temperature Flexibility
	Oil Resistant
	Stain Resistant
Uses	Adhesives
	Automotive Applications
	Seals
	Tubing

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.970	g/cm <sup>3</sup>	ASTM D297
Mooney Viscosity (ML 1+4, 100°C)	43 to 57	MU	ASTM D1646
ACN Content - Bound	28.0 to 31.0	wt%	Internal Method
Ash Content	< 0.8	wt%	ASTM D5667
Volatile Matter	< 1.0	wt%	ASTM D5668

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT