# Caltex PP M560

### Polypropylene Impact Copolymer

#### **GS Caltex**

#### Message:

Caltex PP M560 is a Polypropylene Impact Copolymer (PP Impact Copolymer) material. It is available in Asia Pacific for injection molding. Important attributes of Caltex PP M560 are:

Flame Rated

High Flow

Impact Resistant

Typical applications include:

Appliances

Automotive

Electrical/Electronic Applications

Housings

**Industrial Applications** 

General Information				
UL YellowCard	E319107-100074935	E119841-220392	E352041-101083973	
Features	High Flow			
	High Impact Resistance			
Uses	Appliance Components			
	Automotive Applications			
	Battery Cases			
	Electrical Parts			
	Industrial Applications			
Forms	Pellets			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	0.900	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (230°C/2. kg)	16 27	g/10 min	ASTM D1238	
Molding Shrinkage			ASTM D955	
Flow	1.5 to 1.8	%		
Across Flow	1.5 to 1.8	%		
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	95		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	30.4	MPa	ASTM D638	
Tensile Elongation			ASTM D638	
Yield	10	%		
Break	> 200	%		
Flexural Modulus	1370	MPa	ASTM D790A	

Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	69	J/m	ASTM D256
Gardner Impact	13.7	J	ASTM D3029
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0	).45		
MPa, Unannealed)	125	°C	ASTM D648
Vicat Softening Temperature	152	°C	ASTM D1525
Flammability	Nominal Value		Test Method
Flame Rating	НВ		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

