Dural 202/3 CLEAR 0003

Rigid Polyvinyl Chloride

AlphaGary

Message:

DURAL 202/3 CLEAR 0003 IS A RIGID PVC FORMULATION DESIGNED FOR INJECTION MOLDING. THIS COMPOUND IS PRODUCED FROM FDA SANCTIONED INGREDIENTS AND CAN BE USED FOR A WIDE RANGE OF MEDICAL AND OTHER GENERAL PURPOSE APPLICATIONS

General Information				
Features	Good Thermal Stability			
	High Flow			
	High Impact Resistance			
	Non-Toxic			
Uses	General Purpose			
	Medical/Healthcare Applications			
Agency Ratings	FDA Unspecified Rating	FDA Unspecified Rating		
RoHS Compliance	Contact Manufacturer	Contact Manufacturer		
Appearance	Clear/Transparent	Clear/Transparent		
Forms	Pellets			
Processing Method	Extrusion			
	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.31 to 1.35	g/cm³	ASTM D792	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore D, 15 sec,			ACTA D2240	
mm)	73 to 79	11.2	ASTM D2240	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Modulus	2620	MPa	ASTM D638	
Tensile Strength (1.91 mm)	50.1	MPa	ASTM D638	
Flexural Modulus (3.18 mm)	2610	MPa	ASTM D790	
Flexural Strength (Yield)	82.9	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (23°C)	75	J/m	ASTM D256A	
Flammability	Nominal Value		Test Method	
Flame Rating			UL 94	
0.762 mm ¹	НВ			
0.762 mm	V-0			
Injection	Nominal Value	Unit		
Processing (Melt) Temp	174 to 179	°C		

Extrusion	Nominal Value	Unit
Cylinder Zone 1 Temp.	154	°C
Cylinder Zone 2 Temp.	166	°C
Cylinder Zone 3 Temp.	177	°C
Cylinder Zone 4 Temp.	182	°C
Cylinder Zone 5 Temp.	182	°C
Adapter Temperature	182	°C
Melt Temperature	177 to 188	°C
Die Temperature	182	°C
NOTE		
1.	Horizontal Burn	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

