

ADMER™ NF908E

Linear Low Density Polyethylene

Mitsui Chemicals Europe GmbH

Message:

ADMER® NF908E is a maleic anhydride grafted, LLDPE-based grade, which is designed for adhesion to PA or EVOH in sheet, blown and cast film, double-bubble and triple-bubble applications.

General Information			
Features	Food Contact Acceptable Good Adhesion		
Uses	Adhesives Blown Film Cast Film Film Food Service Applications Non-specific Food Applications		
Agency Ratings	FDA 21 CFR 175.105		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	2.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	40		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	34.0	MPa	ASTM D638
Tensile Elongation (Break)	> 500	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact (Area)	No Break		ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	70.0	°C	ASTM D1525
Peak Melting Temperature	100	°C	ASTM D3418

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

