EcolGreen EGS515S

Polylactic Acid

EcolBiotech Co., Ltd

Message:

Grade for sheets

Physical properties applicable to PVC, PS and PP applicable to cards, trays and decoration sheets, etc

General Information		
Features	Biocompatible	
	Biodegradable	
	Compostable	
	Crystalline	
Uses	Sheet	
Agency Ratings	EC 1907/2006 (REACH)	
RoHS Compliance	RoHS Compliant	
Processing Method	Sheet Extrusion	
Physical	Nominal Value	Unit
Specific Gravity	1.33	g/cm ³
Water Absorption (Equilibrium)	0.46	%
Mechanical	Nominal Value	Unit
Tensile Strength	38.4	MPa
Impact	Nominal Value	Unit
Impact Strength	69.0 to 83.0	J/m
Heat Resistance	70	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

