

# ELASTOSIL® C 150 A/B

Silicone

Wacker Chemie AG

## Message:

Silicone Rubber, RTV-2

spray up technique, Automotive & Transportation

Resin Transfer Molding (RTM), Composites

hand lay up technique, Composites

spray up technique, Composites

hand lay up technique, Automotive & Transportation

Potting Compound, Electronics

Mold Making, Composites

Mold Making, Automotive & Transportation

Mold Making, Construction

Mold Making, Mold Making

General Information			
Uses	Mold Making		
	Vacuum Bagging Film		
Processing Method	Resin Transfer Molding		
Uncured Properties	Nominal Value	Unit	Test Method
Color	Clear/Transparent		
Cured Properties	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	25		ISO 868
Tensile Strength	5.00	MPa	ISO 37
Tensile Elongation at Break	500	%	ISO 37
Tear Strength	25.0	kN/m	ASTM D624B

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

