

# TAISOX 7620M

Ethylene Vinyl Acetate Copolymer

Formosa Plastics Corporation

## Message:

TAISOX 7620M is an Ethylene Vinyl Acetate Copolymer (EVA) material. It is available in Asia Pacific, Europe, or North America for extrusion coating or injection molding.

Important attributes of TAISOX 7620M are:

Copolymer

Crosslinkable

Good Processability

Good Sealability

Typical applications include:

Coating Applications

Foam

General Information			
Features	Copolymer		
	Crosslinkable		
	Good Heat Seal		
	Good Processability		
Uses	Coating Applications		
	Foam		
	Laminates		
Forms	Pellets		
Processing Method	Extrusion Coating		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.930	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	9.0	g/10 min	ASTM D1238
Vinyl Acetate Content	9.0	wt%	
Hardness	Nominal Value	Unit	Test Method
	46		
Durometer Hardness (Shore A)	96		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
Yield	3.92	MPa	
Break	12.7	MPa	

Tensile Elongation (Break)	700	%	ASTM D638
Flexural Modulus	23.5	MPa	ASTM D790
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	30	μm	
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-70.0	°C	ASTM D746
Vicat Softening Temperature	73.0	°C	ASTM D1525
Melting Temperature	95.0	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

