Dion COR-RES 6695FR

Thermoset Polyester

Reichhold Chemicals, Inc.

Message:

Dion COR-RES 6695FR is a Thermoset Polyester product. It can be processed by filament winding, hand lay-up, or laminating and is available in North America. Typical application: Coating Applications. Characteristics include: Chemical Resistant Flame Retardant

General Information			
Features	Flame Retardant Good Chemical Resistance		
Uses	Laminates		
Forms	Pellets		
Processing Method	Filament Winding		
	Hand Lay-up		
	Laminating		
Physical	Nominal Value	Unit	Test Method
Apparent Density	1.25	g/cm³	ASTM D1895
Hardness	Nominal Value	Unit	Test Method
Barcol Hardness (3.18 mm)	47		ASTM D2583
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	3030	MPa	ASTM D638
Tensile Strength (Yield)	55.8	MPa	ASTM D638
Tensile Elongation (Yield)	2.3	%	ASTM D638
Flexural Modulus	3380	MPa	ASTM D790
Flexural Strength (Yield)	89.6	MPa	ASTM D790
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load			
MPa, Unannealed)	132	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

