

Geon™ Vinyl Wire & Cable WJJX207L

Flexible Polyvinyl Chloride

PolyOne Corporation

Message:

Geon™Vinyl Wire & Cable WJJX207L is a flexible PVC product. It can be processed by extrusion coating and is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. Typical application areas are: wire and cable. The main features are: Rohs certification.

General Information			
Uses	Wire and cable applications		
	Wire sheath		
	Communication wire sheath		
Wire Types	CATV		
RoHS Compliance	RoHS compliance		
Forms	Particle		
Processing Method	Extrusion coating		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.35	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw A	82		ASTM D2240
Shaw A, 15 seconds	74		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	11.7	MPa	ASTM D638
Tensile Elongation ² (Break)	340	%	ASTM D638
Aging	Nominal Value	Unit	
Tensile strength retention rate ³ (100°C, 1.91 mm)	100	%	
Elongation retention rate ⁴ (100°C, 1.91 mm)	90	%	
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-30.0	°C	ASTM D746
UL Temperature Rating	75	°C	
Flammability	Nominal Value	Unit	Test Method
Oxygen Index (3.18 mm)	23	%	ASTM D2863
Additional Information			
NOTE: Typical Properties of Molded Slab (0.075"); Not to be Construed as Specifications.Provisional Product Information - Physical and Mechanical properties based on initial production.			
Extrusion	Nominal Value	Unit	
Melt Temperature	166 - 171	°C	
NOTE			

1.	Type 4, 510mm/min
2.	Type 4, 510mm/min
3.	240 hr, UL Standard
4.	240 hr, UL Standard

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

