

Colorite 66 Series 8566

Polyvinyl Chloride

Colorite Polymers

Message:

Colorite 66 Series 8566 is a Polyvinyl Chloride product. It can be processed by extrusion or injection molding and is available in Asia Pacific, Europe, or North America. Applications of Colorite 66 Series 8566 include food contact applications and medical/healthcare.

Characteristics include:

Plasticized

Sterilizable

Low to No Odor/Taste

General Information	
Additive	Plasticizer
Features	Ethylene Oxide Sterilizable
	Low to No Odor
	Non-Phthalate - Citrate Plasticizer
	Radiation Sterilizable
Uses	Medical/Healthcare Applications
	Non-specific Food Applications
Processing Method	Extrusion
	Injection Molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.29	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	85		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus - 100% Secant	13.8	MPa	ASTM D638
Tensile Strength	20.0	MPa	ASTM D638
Tensile Elongation (Break)	300	%	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT