

# NEOFLON™ NC-1539N

Perfluoroethylene Propylene Copolymer

DAIKIN AMERICA, INC.

## Message:

NEOFLON™ NC-1539N is a Perfluoroethylene Propylene Copolymer (FEP) material. It is available in North America.

Typical application of NEOFLON™ NC-1539N: Coating Applications

General Information			
Uses	Coating Applications		
Forms	Powder		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.45 to 0.65	g/cm <sup>3</sup>	JIS K6891
Melt Mass-Flow Rate (MFR) (372°C/2.16 kg)	0.80 to 1.5	g/10 min	ASTM D2116
Particle Size	20.0 to 90.0	µm	Internal Method
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	265 to 275	°C	ASTM D2116

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

