# Generic Elastomer, Specialty

### **Specialty Elastomer**

Generic

#### Message:

This data represents typical values that have been calculated from all products classified as: Generic Elastomer, Specialty This information is provided for comparative purposes only.

| General Information              |               |       |             |
|----------------------------------|---------------|-------|-------------|
| Physical                         | Nominal Value | Unit  | Test Method |
| Specific Gravity                 | 1.13 to 1.48  | g/cm³ | ASTM D792   |
| Hardness                         | Nominal Value | Unit  | Test Method |
| Durometer Hardness (23°C)        | 92 to 96      |       | ASTM D2240  |
| Elastomers                       | Nominal Value | Unit  | Test Method |
| Tensile Stress (Break, 23°C)     | 13.0 to 25.5  | МРа   | ISO 37      |
| Tensile Elongation (Break, 23°C) | 170 to 850    | %     | ISO 37      |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

