

Kumho EPS GN30

Expanded Polystyrene

Korea Kumho Petrochemical Co., Ltd.

Message:

Features: General

Applications: Packing materials, Box,

General Information			
Features	General Purpose		
Uses	General Purpose Packaging		
Physical	Nominal Value	Unit	Test Method
Density	0.0200	g/cm ³	Internal Method
Water Absorption	0.300	g/100 cm ²	Internal Method
Molded Density	20.0 to 25.0	kg/m ³	Internal Method
Compressive Strength	0.100	MPa	Internal Method
Bead Size	500.0 to 600.0	μm	Internal Method
Blowing Agent	5.0	%	Internal Method
Flexural Demolition Load	27	N	Internal Method
Optimum Expansion Multiple	65.0		Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

