

DOW™ HDPE 83754T

High Density Polyethylene Resin

The Dow Chemical Company

Message:

For injection molding applications

Fully thermal and UV stabilized for outdoor use

For beverage crates, pails and buckets

Complies with:

U.S.FDA 21 CFR 177.1520 (c) 3.2A

Europe: Commission Regulation (EU) No 10/2011

Consult the regulations for complete details.

General Information			
Additive	Heat Stabilizer		
	UV Stabilizer		
Agency Ratings	EU No 10/2011		
	FDA 21 CFR 177.1520(c) 3.2a		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.954	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	3.7	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT