# Trademark PP PPH2000MA

## Polypropylene Homopolymer

## Trademark Plastics Corporation

### Message:

Trademark PP PPH2000MA is a Polypropylene Homopolymer (PP Homopolymer) product. It can be processed by injection molding and is available in North America. Applications of Trademark PP PPH2000MA include caps/lids/closures, containers, food contact applications, kitchenware and packaging. Characteristics include: Low to No Odor/Taste Antistatic Food Contact Acceptable Good Processability Homopolymer

General Information				
Additive	Antistatic			
	Nucleating Agent			
Features	Antistatic			
	Food Contact Acceptable			
	Good Color Stability			
	Good Flow			
	Good Processability			
	Homopolymer			
	Low to No Odor			
	Low to No Taste			
	Nucleated			
Uses	Closures			
	Rigid Packaging			
	Table Products			
	Thin-walled Containers			
Agency Ratings	FDA 21 CFR 177.1520			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Density	0.900	g/cm <sup>3</sup>	ASTM D1505	
Melt Mass-Flow Rate (MFR) (230°C/2.16				
kg)	20	g/10 min	ASTM D1238	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength <sup>1</sup> (Yield)	39.3	MPa	ASTM D638	
Tensile Elongation <sup>2</sup> (Yield)	8.0	%	ASTM D638	
Flexural Modulus	1930	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	

Notched Izod Impact (23°C)	32	J/m	ASTM D256
NOTE			
1.	51 mm/min		
2.	51 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

