SILPURAN® 8020/70

Silicone

Wacker Chemie AG

Message:

Cured Properties

Silicone Rubber, HTV
Gaskets, Plastics and Rubber Processing
Membranes, Pharmaceuticals & Healthcare
Balloons, Pharmaceuticals & Healthcare
Seals (HealthCare / Pharma), Pharmaceuticals & Healthcare
Valves (HealthCare / Pharma), Pharmaceuticals & Healthcare

General Information											
Features	Biocompatible BPA Free Breathable Good Chemical Resistance Good Flexibility Good Sterilizability Good Thermal Stability High Gas Permeability High Heat Resistance High Purity Low to No Odor Low to No Water Absorption										
							Non-Toxic				
							Steam Resistant				
						Uses	Body Implants				
							Medical Devices				
							Medical/Healthcare Applications				
							Pharmaceuticals				
						Agency Ratings	ISO 10993				
							USP Class VI				
						Processing Method	Compression Molding				
Press Molding											
	N 11/1	Unit	Test Method								
Uncured Properties	Nominal Value										
Uncured Properties Color	Clear/Transparent	Offic	rest weated								

Unit

Test Method

Nominal Value

Shore Hardness (Shore A)	70		DIN 53505
Tensile Strength	10.4	MPa	DIN 53504
Tensile Elongation at Break	650	%	DIN 53504
Compression Set	35	%	DIN ISO 815-B
Tear Strength	37.0	kN/m	ASTM D624B
Rebound Resilience	53	%	DIN 53512

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

