Xuchuan A-7160/B-8260

Thermoplastic Polyurethane Elastomer (Polyester)

Xuchuan Chemical (Suzhou) Co., Ltd

Message:

Xuchuan A-7160/B-8260 is a Thermoplastic Polyurethane Elastomer (Polyester) (TPU-Polyester) product. It is available in Asia Pacific. Applications of Xuchuan A-7160/B-8260 include consumer goods and marine applications. Primary characteristic: low temperature resistant.

General Information				
Features	High Elasticity			
	Hydrolysis Resistant			
	Low Temperature Resistant			
Uses	Footwear			
0303	Marine Applications			
	manie Applications			
Physical	Nominal Value	Unit		
Density	0.550 to 0.700	g/cm³		
Density				
A-7160 : 40°C	1.010 to 1.020	g/cm³		
B-8260 : 40°C	1.080 to 1.200	g/cm³		
Viscosity				
A-7160 : 40°C	1.00 to 1.40	Pa·s		
B-8260 : 40°C	0.700 to 1.10	Pa·s		
Ross Flex (-20°C) ¹	No Crack			
Cream Time	8.0 to 10.0	sec		
End of Rise Time	50.0 to 60.0	sec		
Free Rise Foam Density	260 to 290	kg/m³		
Preheat Temperature				
Part A	50 to 60	°C		
Part B	50 to 60	°C		
Preheat Time				
Part A	6.0 to 8.0	hr		
Part B	8.0 to 12.0	hr		
Processing Temperature				
Part A	40 to 45	°C		
Part B	38 to 42	°C		
Hardness	Nominal Value	Unit		
Durometer Hardness (Shore A)	65 to 72			
Elastomers	Nominal Value	Unit		
Tensile Strength (Break)	8.50 to 10.0	MPa		

Tensile Elongation (Break)	500 to 680	%
Tear Strength	34.0 to 45.0	kN/m
Thermoset	Nominal Value	Unit
Thermoset Components		
Part A	Mix Ratio by Weight: 100	
Part B	Mix Ratio by Weight: 110	
Demold Time	5.0 to 7.0	min
Injection	Nominal Value	Unit
Mold Temperature	45.0 to 55.0	°C
NOTE		
1.	40000 cycles, Break length 4 mm	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

