

Ad-Tech Epoxy EC-418

Epoxy; Epoxide
Ad-Tech Plastic Systems Corp.

Message:

Ad-Tech Epoxy EC-418 is an Epoxy; Epoxide (Epoxy) product. It can be processed by casting and is available in North America. Typical application: Marine Applications.

General Information			
Uses	Marine Applications		
Appearance	Blue		
Forms	Pellets		
Processing Method	Casting		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.81	g/cm ³	ASTM D1895
Molding Shrinkage - Flow	0.50	%	ASTM D955
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	50		ASTM D2240
Thermoset	Nominal Value	Unit	Test Method
Thermoset Components			
Hardener	Mix Ratio by Weight: 100		
Resin	Mix Ratio by Weight: 100		
Pot Life	100 to 150	min	
Thermoset Mix Viscosity (25°C)	25000	cP	ASTM D2393
Demold Time (80°C)	1100 to 1400	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT