

Daelim Po1y® LH7200

High Density Polyethylene

DAELIM INDUSTRIAL CO., LTD.

Message:

Daelim Po1y® LH7200 is a High Density Polyethylene product. It can be processed by film extrusion and is available in Asia Pacific. Applications of Daelim Po1y® LH7200 include bags/liners, film and food contact applications.

Characteristics include:

Good Processability

Good Sealability

General Information			
Features	Good Heat Seal		
	Good Processability		
	Good Stability		
	High Elongation		
Uses	Bags		
	Film		
Agency Ratings	ASTM D 1248, III, Class A, Cat. 5		
	FDA 21 CFR 177.1520		
Forms	Pellets		
Processing Method	Film Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.948	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.070	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D882
MD : Break	52.0	MPa	
TD : Break	47.1	MPa	
Tensile Elongation			ASTM D882
MD : Yield	470	%	
TD : Yield	580	%	
Dart Drop Impact	200	g	ASTM D1709
Elmendorf Tear Strength			ASTM D1922
MD	30	g	
TD	200	g	
Extrusion	Nominal Value	Unit	
Melt Temperature	180 to 210	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

