

YUPLENE® B920F

Polypropylene Impact Copolymer

SK Global Chemical

Message:

YUPLENE® B920F is a Polypropylene Impact Copolymer (PP Impact Copolymer) product. It is available in Asia Pacific, Europe, or North America. Typical application: Food Contact Applications.

General Information			
Agency Ratings		FDA 21 CFR 177.1520	
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.5	g/10 min	ASTM D1238
Spiral Flow	50.0	cm	Internal Method
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	85		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	27.5	MPa	ASTM D638
Tensile Elongation (Break)	> 500	%	ASTM D638
Flexural Modulus	1370	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	250	J/m	ASTM D256
Aging	Nominal Value	Unit	Test Method
Oven Aging - in Air (150°C)	15.0	day	ASTM D3012
Heat Deflection Temperature	110	°C	ASTM D648
DuPont Impact Strength	> 1.96	J	ASTM D2794
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	150	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT